



**8 John Walsh Boulevard, Suite 417
Peekskill, New York 10566**

**Telephone (914) 739-2885
Fax (914) 739-5204**

IROX BLUE MOVING IRON PHONO CARTRIDGE Owner's Manual and Technical Description

rev2

Mounting Instructions

The IROX BLUE has the ability to accept long mounting screws into its body due to the unique design. You do not need to use screws of an exact required length. You must, however, make sure that when the screws enter that they are threaded correctly. They should not bind, or cross thread. If you encounter difficulty inserting the screws while turning, stop immediately and make sure the screws are the proper 2.5mm metric thread, and that you have not started them in at an improper angle.

You may want to obtain the SoundSmith EZ-Mount screws for your IROX BLUE as our EZ-Mount screws made of both nylon and metal, as well as other non magnetic screws of varying lengths. The nylon washers with the kit are LOCKING type, and must be threaded onto any screw you use. If you wish to shorten any screw, it is advisable to first install a supplied nut that come with the kit, and after shortening the screws, remove the nut to repair the threads.

Electrical Loading

The IROX BLUE is designed to be used with a Moving Magnet Preamp with a gain of 40-46dB .

The new IROX BLUE requires a load of 47K Ohms. Capacitive loading will affect the upper midrange and high end performance. Use between 100 and 300 PF, or more to taste.

Please also note that some designs of “current amplifier” or transconductance preamp circuit designs will not allow loading in the range required, causing the IROX BLUE to sound very dull – caused by improper loading, resulting in loss of high frequencies.

Unlike other cartridges, the IROX BLUE is a six sided fully shielded cartridge, and being such, is one of the world's most hum-free and RF free cartridges. When properly used with shielded cable from your tone-arm, there should be no hum whatsoever.

Tracking Force

The IROX BLUE is designed to operate between 1.8 and 2.4 grams. Optimal force is usually 2.2 grams. Higher VTF may be used, but may result in the cartridge eventually “bottoming” on the record. The cartridge is designed such that no damage will occur to the record or cartridge when that happens.

Hookup

Normal color codes are used for hookup: as viewed from the rear of the cartridge in the normal position, RED is top right, White is top left. Grounds are below them, green on the right, BLUE on the left.

Questions, questions, questions....

“Does the IROX BLUE require special stylus cleaning??

The answer is YES.

CLEANING:

How do I clean the stylus?? Do I use a wet cleaner each time, or often?NO!!!

A DRY soft brush is somewhere between good and “OK”, **but it is far better is to use some “BLUE - Stik”** – this is the Blue clay-like stuff you get in the hardware store stationery department that is used to stick papers and light things to the wall without damaging the wall surface. Use it just before or after every play. Squash a small amount flat onto a heavy coin – such as a quarter. Then place THAT coin on the platter. Cue DOWN and up on the COIN several times. Be VERY care full not to DRAG the coin or turn the platter when the stylus is down on the Blue-Stik or you risk damaging the stylus or cartridge.

Do this several times, each time slightly moving the coin to a new spot when the stylus is raised, so that when it comes down it hits a new spot.

Using this method every record should eliminate the need to wet clean ever, BUT if this doesn’t cure a distortion problem due to debris build up, THEN either use the supplied brush and some RUBBING alcohol (minimum 70% - NO COLORING OR FRAGRANCE) and gently stroke the stylus back to front only. Only wet clean when the dry cleaning doesn’t work.

DO NOT WET CLEAN OFTEN - TO DO SO WILL POTENTIALLY CAUSE SEVERE DAMAGE TO THE STYLUS MOUNTING AND CAUSE THE DIAMOND TO COME OFF. USE THE ABOVE BLUE-STIK METHOD. DO not use any stylus cleaner other than alcohol. To do so will damage the cartridge.

If you don't have a good VERY SOFT stylus brush, purchase a WATERCOLOR brush with non-synthetic fibers, one that has bristles that are about 1/8" in cross section. CUT the bristles straight across with a small scissors, making them about 1/8" long. Break or cut off the wood handle so the brush is VERY SHORT, and has very little wood handle. This will minimize accidents and reduce jitter when handling and using.

RECORD CLEANING:

DO NOT TALK towards your records. They are neither listening, nor do they need a talking to. You need to listen to them. The reason is this: when you talk, you spit. Yes, even you. Fine drops. You cannot see them because the record is textured with grooves. When the stylus hits the dried spit, this GLUE then sticks to all the dirt and dust in the grooves. It only takes a few revolutions for this to happen, and so much debris can build up on the stylus, **you will have worse than distortion** – The stylus may not even track the record...as below.....



< BEFORE AFTER >>



What do I suggest?? A record cleaner – It's a MUST HAVE item for any record enthusiast. How much do you invest in one?? As much as you are able – the return will be many times its cost.

Cleaning your records well is the BEST investment you can make in protecting that great sound of your analog system.

How long will my IROX BLUE stylus last?

All diamond styli last approximately 700 hours when aligned and used correctly. Soundsmith can re-tip your IROX BLUE in or out of warranty. The IROX BLUE is fully warranted against manufacturing defect for a period of TWO YEARS to the original owner. **Unlike many other manufacturers of fine cartridges, you will find that The Soundsmith is very interested in protecting your investment over the long term. If the IROX BLUE suffers a non-warranty failure due to severe mishandling, it can be fully rebuilt at this time for \$360 maximum charge.**

How long will my IROX BLUE last?

Due to the nature of the stylus mounting, dry cleaning the stylus is especially

important with the IROX BLUE design. Do it EVERY time you play, using Blu-Stik (from DAP) obtainable at a hardware store.

We have included alignment instructions below which you are strongly encouraged to read and follow. Although the IROX BLUE will perform satisfactorily without critical alignment, we strongly advise you do attempt to do so, just as you would balance the tires on your car before expecting the best performance from them. It is strongly advisable therefore, to perform cartridge alignments to the best of your ability. One must therefore align an advanced stylus design carefully and correctly to enjoy its benefits. While some expensive cartridge designs employ lower cost, less aggressive styli shapes and therefore enjoy the benefit of ease of alignment, they can also suffer at times from less than optimal performance. We made the decision to use one of the best stylus shapes available, to allow those who demand the best performance possible to realize such if careful alignment and record care are employed.

Azimuth

An approximate azimuth setting can be viewed by looking at the front of the cartridge, while it is playing mid-point on a record. By looking at the gap between the metal bottom of the cartridge and the record surface, one should attempt to make this gap even. Back-lighting this can help to visualize this gap. Best azimuth is obtained by obtaining equal channel separation via a test record – NOT far off from this position. A fozgometer or other types of azimuth testing gear will likely NOT work with Soundsmith cartridges due to their extreme separation capability.

Stylus Rake Angle – (or VTA)

Normal SRA is achieved when the cartridge, as viewed from the side, has its top FLAT of the body (underneath the headshell) parallel with the surface of the record. This may also correspond with a non-tapered arm being parallel with the record surface. Adjustment up or down from that point will affect the high frequency performance and imaging. There are many suggestions as how to tweak this – far too many to cover here.

Some thoughts about the IROX BLUE

What happens to the energy that is “Stored”? The energy that goes up the cantilever moves the generating element. If that can be made small enough, good things happen. But what happens to the energy that goes into the cartridge body?? The IROX BLUE employs a very unique “Energy Distribution System” to insure that the energy gets into the cartridge body properly, and into the waiting tone arm to be damped. It is one of the features of the IROX BLUE, and one of the major contributing design efforts towards perfection.

Moving mass

Magnetic cartridges have three elements necessary to generate a voltage; a magnet, coil assemblies, and an “iron” or ferrous component of some shape. The performance of any

magnetic cartridge is largely dependent on how little “moving mass” it has; this is both the mass of the stylus at the end of the cantilever, as well as the total mass of the voltage generating parts that the stylus must move. While there are some advantages to specific designs, both moving magnet and moving coil cartridges are at a distinct disadvantage in regard to moving mass as they are required to move either a relatively large magnet, or a “coil assembly”. The coil assembly in reality is a series of wire windings often on a metal core, more properly labeled as an “armature”.

In a moving iron design, one has the potential to reduce the moving mass to a very small value by virtue of the having the required two relatively massive elements (coils and magnet) held in fixed position. It is important to understand that while it is true that all designs have trade-offs, a designer must arrange the order of trade-offs carefully. Reducing moving mass is at the top of the list for Soundsmith; less inertia in the generating elements means faster starts and faster stops. It also means a much easier job of damping the unwanted “ringing” of the moving system, a system that must make sudden, accurate and controlled directional changes to follow the grooves of a record.

In order to obtain accurate vinyl reproduction, the stylus must remain in near constant contact with the groove walls. The larger the moving mass, the greater the jittering of the stylus, meaning that it is in reality taking “samples” of the groove walls from moment to moment, and averaging or guessing at what is taking place in between those samples. A “digital” sort of rendering, if you will. Lower mass? Less jitter. Less jitter means more time in contact with the groove, which means detail and micro detail. If a cartridge can’t stay in contact with the groove walls, you can’t hear everything that is on the record. In a very real sense, it’s that simple.

The obvious question, “Why doesn’t everyone make cartridges this way, if reducing the moving mass is an absolute requirement for accuracy?” the answer to that is simple as well. It’s very hard to do so. A properly designed Moving Iron cartridge requires an ultra-high level of precision in manufacturing, and potentially low product yield. It is not the best path for profitability, only sonic ability.

Another advantage of this design is the inherent high level of channel separation. Unlike MC cartridges, a rotation of the generating element in The IROX BLUE (moving iron) due to manufacturing tolerances or aging does not affect the separation at all. Furthermore, unlike moving coil cartridges, our Moving Iron designs CANNOT rotate out of position, maintaining the critical azimuth position for the life of the cartridge.

It is our hope that your carefully crafted, hand-made Soundsmith IROX BLUE cartridge will bring you many years of listening pleasure. The simple fact is, when we sit at a microscope for hours making each one, that is primary in our thoughts.....we hope that each one will bring some joy to the listener.

Peter Ledermann / President.